



VIEW ON 'X'
 HOLE TAPPED M16 X 36mm DEEP
 TO DIN 332 FORM 'D'

TERMINAL BOX POSITION : - CAN BE ARRANGED AT EITHER 9, 12 OR 3 O'CLOCK BY MOVING FEET
 TERMINAL BOX POSITION:- CAN BE ARRANGED AT EITHER 9,12 OR 3 O'CLOCK.
 STANDARD TERMINAL BOX POSITION IS 12 O'CLOCK AS SHOWN.
 CONDUIT ENTRIES:- TERMINAL BOX CAN BE ROTATED AT 90°INTERVALS
 (CONDUIT ENTRY POSITION SHOWN FOR ILLUSTRATION ONLY).

ALL DIMENSIONS IN MILLIMETERS	
	FIRST ANGLE PROJECTION
BROOK CROMPTON	
Produced by <i>Tamel S.A.</i> a company of ATB	
DRG. No.	W41GH0108T
DRG. REF.	
REVISION:	DATE:

SHEET
 SIZE
A3

TITLE:
**OUTLINE DIMENSION DRAWING W CAST IRON TOTALLY ENCLOSED FAN COOLED
 160M/L FRAME FOOT & D-FLANGE MOUNTED MOTOR - TERMINAL BOX TOP**

	NAME	DATE
DRAWN	JM	10-07-10
CHECKED		
SCALE	N.T.S.	