

### Three-phase asynchronous motor

MOTOR FRAME: **Aluminium**

a company of



Motor type: **WU-DA112MM-H IE2 2P 4kW B35**  
 Motor item number: **112W267220T**

Rated power:				<b>4 kW</b>		<b>kW</b>
Poles(Synch speed):				<b>2p (3000) r.p.m</b>		<b>r.p.m</b>
Full load speed:				<b>2870 r.p.m</b>		<b>r.p.m</b>
Voltage:	<b>50 HZ data</b>	<b>400</b>	<b>/</b>	<b>690</b>	<b>V</b>	<b>V</b>
Frequency:				<b>50</b>	<b>Hz</b>	<b>Hz</b>
Connection:		<b>Δ</b>	<b>/</b>	<b>Y</b>		
Amps full load (FLA):		<b>7,3</b>	<b>/</b>	<b>4,2</b>	<b>A</b>	<b>A</b>
Amps no-load (NLA):					<b>A</b>	
						<b>60 HZ data</b>

Enclosure:	<b>IP55</b>	Cable entries size:	<b>2 x CM25</b>
Mounting:	<b>IM B35 (IM 2001)</b>	Winding protection:	
Insulation Class:	<b>F</b>	Max. Altitude:	<b>1000 m.a.s.l.</b>
Max. ambient temp.:	<b>+40 °C</b>	Heater:	<b>no</b>
Min. ambient temp.:	<b>-20 °C</b>	Shaft extension:	<b>28x60 mm</b>
Max. temp. rise:	<b>80 K</b>	Weight:	<b>kg</b>
Duty type:	<b>S1</b>	Painting:	<b>Alkyd-Amin Resins Paint</b>
Cooling form:	<b>IC411 (TEFC)</b>	Color:	<b>RAL 5021</b>
Bearing DE	<b>6206 ZZ C3</b>	Box position:	<b>Top DE</b>
Bearing NDE	<b>6205 ZZ C3</b>	Cable entry towards:	<b>Right</b>
Grease:	<b>Lithium or Polyurea Base</b>	Cable type:	<b>N/A</b>
Regreasing facilities:	<b>NO</b>	Balance grade:	<b>Normal</b>

Efficiency class:	<b>IE2</b>	Sound pressure (1m):	<b>60 dB(A)</b>
Load data:	<b>100% 75% 50%</b>	Resistance R20:	<b>3,53 PH</b>
Efficiency:	<b>85,8 89,2 87,4</b>		
Power factor:	<b>0,91 0,88 0,81</b>		

Full load torque (FLT):	<b>13,3 Nm</b>	Pull out torque ratio:	<b>3,1 MK/MN</b>
Starting torque ratio:	<b>3,0 MA/MN</b>	Pull up torque:	<b>2,8 MS/MN</b>
Starting current ratio:	<b>7,8 IA/IN</b>	Rotor inertia WK2:	<b>0,008 kgm<sup>2</sup></b>

Special remarks:

#### SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:
Certificate number:	t <sub>E</sub> time: <b>sek</b>

Special remarks: