

Three-phase asynchronous motor

MOTOR FRAME: **Aluminium**

www.tamel.pl

Produced by **Tamel S.A.** a company of



Motor type: **WU-DA132SJX-D IE2 2P 7,5kW B5**
Motor item number: **132W327211T**

Rated power:	7,5 kW				kW
Poles(Synch speed):	2p (3000) r.p.m				r.p.m
Full load speed:	2900 r.p.m				r.p.m
Voltage:	400	/	690	V	V
Frequency:	50 Hz				Hz
Connection:	Δ	/	Y		
Amps full load (FLA):	13,5	/	7,8	A	A
Amps no-load (NLA):					A

Enclosure:	IP55		Cable entries size:	2 x CM25	
Mounting:	IM B5 (IM 3001)		Winding protection:		
Insulation Class:	F		Max. Altitude:	1000	m.a.s.l.
Max. ambient temp.:	+40	°C	Heater:	no	
Min. ambient temp.:	-20	°C	Shaft extension:	38x80	mm
Max. temp. rise:	80	K	Weight:	kg	
Duty type:	S1		Painting:	Manufacturer standard	
Cooling form:	IC411 (TEFC)		Color:	RAL 5021	
Bearing DE	6208	ZZ C3	Box position:	Top DE	
Bearing NDE	6305	ZZ C3	Cable entry towards:	Right	
Grease:	standard		Cable type:	N/A	
Regreasing facilities:	NO		Balance grade:	Normal	

Efficiency class:	IE2			Sound pressure (1m):	dB(A)
Load data:	100%	75%	50%	Resistance R20:	1,58 PH
Efficiency:	88,1	88,5	88,5		
Power factor:	0,91	0,88	0,82		

Full load torque (FLT):	24,7	Nm	Pull out torque ratio:	MK/MN	
Starting torque ratio:	2,5	MA/MN	Pull up torque:	MS/MN	
Starting current ratio:	8,2	IA/IN	Rotor inertia WK2:	kgm ²	

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:	
Certificate number:	t _E time:	sek

Special remarks: