

Three-phase asynchronous motor

MOTOR FRAME: **Aluminium**

a company of



Motor type: **WU-DA132MVX IE2 4P 7,5kW B3**
 Motor item number: **132W327401T**

Rated power:	7,5 kW			kW
Poles(Synch speed):	4p (1500) r.p.m			r.p.m
Full load speed:	1460 r.p.m			r.p.m
Voltage:	400	/	690	V
Frequency:	50 Hz			Hz
Connection:	Δ	/	Y	
Amps full load (FLA):	14,7	/	8,5	A
Amps no-load (NLA):				A

Enclosure:	IP55		Cable entries size:	2 x CM25
Mounting:	IM B3 (IM 1001)		Winding protection:	
Insulation Class:	F		Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40	°C	Heater:	no
Min. ambient temp.:	-20	°C	Shaft extension:	38x80 mm
Max. temp. rise:	80	K	Weight:	50 kg
Duty type:	S1		Painting:	Alkyd-Amin Resins Paint
Cooling form:	IC411 (TEFC)		Color:	RAL 5021
Bearing DE	6208	ZZ C3	Box position:	Top DE
Bearing NDE	6305	ZZ C3	Cable entry towards:	Right
Grease:	Lithium or Polyurea Base		Cable type:	N/A
Regreasing facilities:	NO		Balance grade:	Normal

Efficiency class:	IE2			Sound pressure (1m):	59 dB(A)
Load data:	100%	75%	50%	Resistance R20:	1,26 PH
Efficiency:	88,7	89,4	88,6		
Power factor:	0,83	0,76	0,67		

Full load torque (FLT):	49,1	Nm	Pull out torque ratio:	3,2	MK/MN
Starting torque ratio:	2,9	MA/MN	Pull up torque:	2,5	MS/MN
Starting current ratio:	8,1	IA/IN	Rotor inertia WK2:	0,033	kgm²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:	
Certificate number:	t _E time:	sek

Special remarks: