

Three-phase asynchronous motor

MOTOR FRAME: **Cast Iron**

a company of 

Motor type: **WU-DF160MB IE2 2P 11 kW B3**
Motor item number: **160W417300T**

Rated power:	11 kW			60 HZ data	kW
Poles(Synch speed):	2p (3000) r.p.m			50 HZ data	r.p.m
Full load speed:	2940 r.p.m			60 HZ data	r.p.m
Voltage:	400	/	690 V	50 HZ data	V
Frequency:	50 Hz			60 HZ data	Hz
Connection:	Δ	/	Y	50 HZ data	
Amps full load (FLA):	20	/	11,5 A	60 HZ data	A
Amps no-load (NLA):	A			60 HZ data	A

Enclosure:	IP55	Cable entries size:	2 x CM32
Mounting:	IM B3 (IM 1001)	Winding protection:	
Insulation Class:	F	Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40 °C	Heater:	no
Min. ambient temp.:	-20 °C	Shaft extension:	42x110 mm
Max. temp. rise:	80 K	Weight:	121 kg
Duty type:	S1	Painting:	Argus
Cooling form:	IC411 (TEFC)	Color:	RAL 5021
Bearing DE	6309 ZZ C3	Box position:	Top DE
Bearing NDE	6307 ZZ C3	Cable entry towards:	Right
Grease:	Lithium or Polyurea Base	Cable type:	N/A
Regreasing facilities:	NO	Balance grade:	Normal

Efficiency class:	IE2	Sound pressure (1m):	68 dB(A)
Load data:	100% 75% 50%	Resistance R20:	0,85 PH
Efficiency:	89,4 89,7 88,5		
Power factor:	0,89 0,84 0,76		

Full load torque (FLT):	35,7 Nm	Pull out torque ratio:	3,0 MK/MN
Starting torque ratio:	2,2 MA/MN	Pull up torque:	1,8 MS/MN
Starting current ratio:	7,8 IA/IN	Rotor inertia WK2:	0,039 kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:
Certificate number:	t _E time: sek

Special remarks: