

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: **Cast Iron**

a company of



Motor type: **W-DF250SN IE2 4P 55kW B3**
Motor item number: **250W931406**

Rated power:	55 kW				kW
Poles(Synch speed):	4p (1500) r.p.m				r.p.m
Full load speed:	1475 r.p.m				r.p.m
Voltage:	400	/	690		V
Frequency:	50 Hz				Hz
Connection:	Δ	/	Y		
Amps full load (FLA):	98	/	56,6		A
Amps no-load (NLA):					A

Enclosure:	IP55		Cable entries size:		
Mounting:	IM B3 (IM 1001)		Winding protection:	3xPT160	
Insulation Class:	F		Max. Altitude:	1000	m.a.s.l.
Max. ambient temp.:	+40	°C	Heater:	no	
Min. ambient temp.:	-20	°C	Shaft extension:	70x140	mm
Max. temp. rise:	80	K	Weight:	570	kg
Duty type:	S1		Painting:	Argus	
Cooling form:	IC411 (TEFC)		Color:	RAL 5021	
Bearing DE	6316	C3	Box position:	Top DE	
Bearing NDE	6316	C3	Cable entry towards:	Right	
Grease:	Lithium or Polyurea Base		Cable type:	N/A	
Regreasing facilities:	YES		Balance grade:	Normal	

Efficiency class:	IE2			Sound pressure (1m):	67 dB(A)
Load data:	100%	75%	50%	Resistance R20:	0,093 PH
Efficiency:	93,5	92,8	92,2		
Power factor:	0,87	0,81	0,76		

Full load torque (FLT):	356,1	Nm	Pull out torque ratio:	3,2	MK/MN
Starting torque ratio:	2,7	MA/MN	Pull up torque:	1,9	MS/MN
Starting current ratio:	7,7	IA/IN	Rotor inertia WK2:	0,65	kgm²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:	
Certificate number:	t _E time:	sek

Special remarks: