

BROOK CROMPTON

TECHNICAL DATA SHEET

Three-phase asynchronous motor

MOTOR FRAME: **Cast Iron**

a company of



Motor type: **WP-UDF355SN IE2 4P 280kW B3**
Motor item number:

Rated power:	280 kW		60 HZ data	kW
Poles(Synch speed):	4p (1500) r.p.m		50 HZ data	r.p.m
Full load speed:	1490 r.p.m		60 HZ data	r.p.m
Voltage:	400 / 690	V	50 HZ data	V
Frequency:	50 Hz		60 HZ data	Hz
Connection:	Δ / Y		50 HZ data	
Amps full load (FLA):	483 / 280	A	60 HZ data	A
Amps no-load (NLA):	A			

Enclosure:	IP55		Cable entries size:	
Mounting:	IM B3 (IM 1001)		Winding protection:	3xPT160
Insulation Class:	F		Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40	°C	Heater:	no
Min. ambient temp.:	-20	°C	Shaft extension:	100x210 mm
Max. temp. rise:	80	K	Weight:	2000 kg
Duty type:	S1		Painting:	Argus
Cooling form:	IC411 (TEFC)		Color:	RAL 5021
Bearing DE	N324	C3	Box position:	Top DE
Bearing NDE	6324	C3	Cable entry towards:	Right
Grease:	Lithium or Polyurea Base		Cable type:	N/A
Regreasing facilities:	YES		Balance grade:	Normal

Efficiency class:	IE2			Sound pressure (1m):	76 dB(A)
Load data:	100%	75%	50%	Resistance R20:	0,008 PH
Efficiency:	95,1	95,7	95,3		
Power factor:	0,88	0,84	0,77		

Full load torque (FLT):	1794,6	Nm	Pull out torque ratio:	2,5	MK/MN
Starting torque ratio:	2,1	MA/MN	Pull up torque:	1,7	MS/MN
Starting current ratio:	7,2	IA/IN	Rotor inertia WK2:	10,6	kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:	
Certificate number:	t _E time:	sek

Special remarks: