

Three-phase asynchronous motor

MOTOR FRAME: Cast Iron

a company of



Motor type: WU-DF160LV IE2 6P 11kW B3
Motor item number: 160W417701T

50 HZ data	Rated power:	11 kW		60 HZ data	kW
	Poles(Synch speed):	6p (1000) r.p.m			r.p.m
	Full load speed:	980 r.p.m			r.p.m
	Voltage:	400 / 690	V		V
	Frequency:	50 Hz			Hz
	Connection:				
	Amps full load (FLA):	24 / 13,8	A		A
	Amps no-load (NLA):				A

Enclosure:	IP55	Cable entries size:	2 x CM32
Mounting:	IM B3 (IM 1001)	Winding protection:	
Insulation Class:	F	Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40 °C	Heater:	no
Min. ambient temp.:	-20 °C	Shaft extension:	42x110 mm
Max. temp. rise:	80 K	Weight:	133 kg
Duty type:	S1	Painting:	Argus
Cooling form:	IC411 (TEFC)	Color:	RAL 5021
Bearing DE	6309 ZZ C3	Box position:	Top DE
Bearing NDE	6307 ZZ C3	Cable entry towards:	Right
Grease:	Lithium or Polyurea Base	Cable type:	N/A
Regreasing facilities:	NO	Balance grade:	Normal

Efficiency class:	IE2	Sound pressure (1m):	59 dB(A)
Load data:	100% 75% 50%	Resistance R20:	0,73 PH
Efficiency:	88,7 90 88,5		
Power factor:	0,75 0,67 0,57		

Full load torque (FLT):	107,2 Nm	Pull out torque ratio:	2,8 MK/MN
Starting torque ratio:	2,0 MA/MN	Pull up torque:	1,9 MS/MN
Starting current ratio:	7,5 IA/IN	Rotor inertia WK2:	0,12 kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:
Certificate number:	t _E time: sek

Special remarks: